

General Details		Units	Fixed Speed - Cooling Only
Nominal Performance Data	Capacity	TR (Nom.)	4.0
		Cooling	KW
	Btu/h		45,731
	EER	w/w	3.04
Indoor Unit Specifications			
Indoor Model		Units	AP48KC1QRA
Electrical Parameters	Power supply	Ph/V/Hz	1Ph/220-240V/50Hz
Performance	Air flow	cfm (H/M/L/SL)	1206/1059/1000/882
		m3/h (H/M/L/SL)	2050/1800/1700/1500
	Sound pressure level (H/M/L/SL)	dB(A)	53/48/45/42
Installation	External dimensions(W/D/H)	mm	600/350/1850
	Shipping dimensions(W/D/H)	mm	693/448/2035
	Net/Shipping weight	kg	59/67
	Wireless Controller	Standard	YL-HBS01
Outdoor Unit Specifications			
Outdoor Model		Units	1U48NC1QAB
Electrical Parameters	Power supply	Ph/V/Hz	3Ph/380-415V/50Hz
Performance	Air flow	cfm (H)	2941
		m3/h (H)	5000
	Sound Pressure Level	dB(A)	61
Installation	External Dimensions(W/D/H)	mm	950/370/965
	Shipping Dimensions(W/D/H)	mm	1050/485/1130
	Net/Shipping Weight	kg	86/92
	Compressor Type	-	Rotary
	Refrigerant Type	-	R-410a
	Refrigerant Liquid Pipe Size	mm	9.52
	Refrigerant Gas Pipe Size	mm	19.05
	Total Pipe Length	m	50
	Max. Pipe Length - Horizontal	m	30
Max. Pipe Length - Vertical	m	20	
Working Temp.	Cooling (Min-Max)	°C	18 ~ 53

Note: Due to our policy of innovations, some specification may be change without any prior information.